
Pure Freude an Wasser

39 112 001 **RAPID SL ELEMENT FOR GROHE SENSIA SHOWER WCS, 1.13 M INSTALLATION HEIGHT**






PRODUCT DESCRIPTION

- with flushing cistern GD 2, 6 - 9 l
- quick adjustment, lockable
- fixing material
- TÜV approved
- 2 WC fixing bolts
- fixing device for ceramic
- distance of fixing bolts 180/230 mm
- PP outlet bend Ø 90 mm
- depth adjustable
- reducer Ø 90/110 mm
- inlet and outlet connecting set
- flushing cistern GD 2, 6 - 9 l, containing following features:
- adjustment ex factory 6 l and 3 l
- pneumatic discharge valve offering 3 modes of operation: dual flush or start/stop or single flush
- water supply from back
- low noise (group I acc. to German Noise Specification)
- insulated against condensation
- 1/2" water supply connection including integrated angle valve and push fit flexible hose union
- no tools required for the installation of the inspection shaft including protection during construction phase
- for vertical or horizontal use
- including wall brackets 38 558 00M for on-the-wall installation
- universal water connection for shower toilets Sensia Arena and Sensia IGS
- concealed socket for mains supply
- positioning help for electrical connection
- for mounting of small flush plates please order revision shaft 40 911 000 (sold separately)

39 112 001 **RAPID SL ELEMENT FOR GROHE SENSIA SHOWER WCS, 1.13 M INSTALLATION HEIGHT**



SPARE PARTS, September 2015 – now

1: Threaded bolt (Order-nr. 4276400M)

2: WC inlet and outlet connecting set (Order-nr. 37311K00)

2.1: Basin fastening (Order-nr. 43511SH0)

2.2: Connector (Order-nr. 37119000)

3: PP-outlet bend Ø 90 mm (Order-nr. 42327000)

4: Transition piece 90/110 to Rapid SL (Order-nr. 42242000)

5: Support for outlet bend (Order-nr. 42243000)

6: Inspection shaft (Order-nr. 66791000)

7: Filling valve (Order-nr. 37095000)

7.1: Lever (Order-nr. 43734000)

7.1.1: Seal (Order-nr. 4377000M)

7.2: Valve head (Order-nr. 43536000)

7.3: Membrane (Order-nr. 4375800M)

7.4: Screw cap (Order-nr. 43735000)

7.5: Valve float, 5 pcs. (Order-nr. 4379100M)

7.6: Set of seals (Order-nr. 43722000)*

8: Support device (Order-nr. 42246000)

9: Connecting hose (Order-nr. 42233000)

9.1: Sealing washer (Order-nr. 0319100M)

10: Dual Flush discharge valve AV1 (Order-nr. 42320000)

10.1: Extension for overflow pipe (Order-nr. 42313000)

10.2: Pneumatic hose (Order-nr. 42319000)

10.3: Seal (Order-nr. 42310000)

11: Valve seat for GD2 (Order-nr. 42315000)

12: Wall brackets (Order-nr. 3855800M)

13: 4.5 l adapter for GD2 (Order-nr. 42333000)*

14: Installation rail (Order-nr. 37310000)*

15: Extension (Order-nr. 38629000)*

16: Retrofit set (Order-nr. 38796000)*

*Special accessories